

UNCLASSIFIED

**AD NUMBER**

AD319088

**CLASSIFICATION CHANGES**

TO: unclassified

FROM: confidential

**LIMITATION CHANGES**

TO:

Approved for public release, distribution  
unlimited

FROM:

**AUTHORITY**

OCA; 31 Dec 1972, IAW document markings;  
USNOL ltr 29 Aug 1974

THIS PAGE IS UNCLASSIFIED

# **GENERAL DECLASSIFICATION SCHEDULE**

**IN ACCORDANCE WITH  
DOD 5200.1-R & EXECUTIVE ORDER 11652**

## **THIS DOCUMENT IS:**

**CLASSIFIED BY** \_\_\_\_\_

**Subject to General Declassification Schedule of  
Executive Order 11652-Automatically Downgraded at  
2 Years Intervals- DECLASSIFIED ON DECEMBER 31, 1972**

**BY**

**Defense Documentation Center**

**Defense Supply Agency**

**Cameron Station**

**Approved: \_\_\_\_\_**

**AD 319 088**

*Reproduced  
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY  
ARLINGTON HALL STATION  
ARLINGTON 12, VIRGINIA**



NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CONFIDENTIAL

NAVORD REPORT

6896

625200.

PITCH DAMPING TESTS OF THE PERSHING RE-ENTRY BODY (U)

CATALOGED BY ASTIA  
AS FILE NO. 319088

10 JUNE 1960

XEROX



RELEASED TO ASTIA BY NAVAL ORDNANCE  
LABORATORY

U. S. NAVY

CONFIDENTIAL

CONFIDENTIAL  
NAVORD Report 6896

Aerodynamics Research Report 110

PITCH DAMPING TESTS OF THE PERSHING RE-ENTRY BODY

Prepared by

V. Schermerhorn  
F. J. DeMeritte

ABSTRACT: This report presents the results of an investigation in the NOL Supersonic Tunnel No. 1 to measure the pitch damping of the Pershing re-entry body.

These data were obtained at Mach numbers 1.76, 2.03, 2.28, 2.76, 3.51, 4.12, and 4.82.

*U.S. Govt. Agencies and  
Military ONLY*

*OTHERS*

DIRECT REQUESTS TO: NAVAL ORDNANCE LAB.  
Silver Springs, MD.

U. S. NAVAL ORDNANCE LABORATORY  
WHITE OAK, MARYLAND

CONFIDENTIAL

NAVORD Report 6896

10 June 1960

The purpose of this investigation was to obtain pitch damping data on the Pershing re-entry body. This investigation was performed at the request of Army Ballistic Missile Agency (reference (a)), under Task Number NOL 455.

This report may include technical data or other information which may be proprietary to parties other than the Government. The transmission by the Department of the Navy of this document is not to be regarded by implication or otherwise as licensing technical data or information disclosed herein for commercial purposes, as distinguished from governmental purposes, or conveying any right or permission to the recipient or any other person or corporation gaining access to this document.

W. D. COLEMAN  
Captain, USN  
Commander

R. KENNETH LOBB  
By direction

CONFIDENTIAL  
NAVORD Report 6896

CONTENTS

	Page
INTRODUCTION.....	1
AERODYNAMIC SYMBOLS.....	1
DESCRIPTION OF THE MODEL AND TEST TECHNIQUES.....	1
DATA REDUCTION.....	2
DISCUSSION.....	2
REFERENCES.....	3

ILLUSTRATIONS

Figure 1      Pershing Re-Entry Body  
Figures 2-5    $C_{M_q} + C_{M_{\dot{\alpha}}}$  versus  $\alpha$



CONFIDENTIAL  
NAVORD Report 6896

PITCH DAMPING TESTS OF THE PERSHING RE-ENTRY BODY

INTRODUCTION

1. The Pershing missile is a medium range ballistic missile being developed by the Army Ballistic Missile Agency.
2. This report gives the results of a wind-tunnel investigation performed to determine the pitch damping of the re-entry body.

AERODYNAMIC SYMBOLS

A	reference cross-sectional area (sq. in)
$C_{M_q} + C_{M_{\dot{\alpha}}}$	aerodynamic damping coefficient ( $-16\mu/\pi\rho Vd^4$ )
c.g.	center of gravity (2.5493 reference diameters from the base)
d	reference diameter (one caliber) (2.25 inches)
Ma	Mach number
I	transverse moment of inertia about the c.g. (slugs-ft <sup>2</sup> )
t	time (sec)
V	velocity (ft/sec)
$\bar{\alpha}$	average angular amplitude (deg)
$\alpha$	angle of attack (deg)
$\alpha_t$	trim angle (deg)
$\rho$	air density (slugs/cu.ft)
$\mu$	dynamic damping coefficient ( $-2I n\alpha/\alpha_o/\Delta t$ )

DESCRIPTION OF THE MODELS AND TEST TECHNIQUE

3. The model was dynamically balanced about the scaled full-scale center of gravity. A shaft whose axis was normal to the longitudinal axis of the model was passed through the center of gravity and was attached to the model by means of precision ball bearings of very low frictional torque. The model was thus able to rotate in the pitch plane about a transverse axis. The model was mounted in the wind tunnel and started to rotating before the wind tunnel was started. The rotating motion of the model becomes an oscillating one when the wind tunnel begins blowing. The model oscillations begin to damp. This motion of the model is recorded with a high-speed motion-picture camera with a film speed of 75 frames per second.

Figure 1 shows a sketch of the model.

CONFIDENTIAL  
NAVORD Report 6896

DATA REDUCTION

4. The evaluation technique is described in detail in reference (b). Briefly the data reduction consists of two phases: reading the film and fitting an envelope to the data obtained from the film. From the film the angle of attack of the model is obtained for each frame of film using a comparator. The time record is obtained from the film speed. The angular deflection plotted against time yields a damped sine motion. The envelope of the motion is faired. Damped harmonic motion requires that the restoring moment be linear; this is not always the case. However, by assuming the harmonic condition for small increments along the envelope, the damping coefficient can be obtained as a function of average angular deflection.


DISCUSSION

5. The data are plotted as  $C_{M_q} + C_{M_{\dot{\alpha}}}$  versus  $\bar{\alpha}$  in Figures 2 through 5. At Mach numbers 1.76 and 2.03 small trim angles were noted.

CONFIDENTIAL  
NAVORD Report 6896

REFERENCES

- (a) Geissler, E. D., Wind-Tunnel Request (WTR-581) 1960
- (b) Shantz, I., and Groves, R. T., "Subsonic Damping-in-Pitch Measurements of the EX-10, EX-30, and 6" Test Vehicle," NAVORD Report 4025, Conf., (1958)



ALL DIMENSIONS IN CALIBERS

FIG. 1 PERSHING RE-ENTRY BODY

CONFIDENTIAL  
 NAVORD REPORT 6896  
 PERSHING  
 $C_{M_q} + C_{M_{\dot{\alpha}}}$  vs  $\dot{\alpha}$





FIG. 2  $C_{M_q} + C_{M_{\dot{\alpha}}}$  versus  $\dot{\alpha}$

PERSHING

$C_{M_q} + C_{M_{\dot{\alpha}}}$  vs  $\frac{1}{\alpha}$

$Ma = 2.28$





FIG. 3  $C_{M_q} + C_{M_{\dot{\alpha}}}$  versus  $\frac{1}{\alpha}$

$C_{Mq} = 0$  vs  $Re$





FIG. 4  $C_{Mq} + C_{Md}$  versus

CONFIDENTIAL  
NAVORD REPORT 6896  
PERMING

$$C_{M_q} + C_{M_{\dot{\alpha}}} \text{ versus } \alpha$$

$$Ma = 3.51$$



$$Ma = 4.82$$




FIG. 5  $C_{M_q} + C_{M_{\dot{\alpha}}}$  versus  $\alpha$

CONFIDENTIAL



**CLASSIFIED**